

## PRESS-RELEASE

11 SEPTEMBER 2018; SAARBRÜCKEN

Innovative combination of hard and soft materials improves adhesion to rough surfaces

Adhesion is involved whenever industrial components are moved to and from without any residues being left behind. But the surfaces of these objects are never completely smooth. Even those surfaces that appear smooth to the human eye tend to be rough when observed under a microscope. Scientists at the Leibniz Institute for New Materials developed a new adhesive structure so that adhesion, even to these types of rough surfaces, can be reliably provided. They combined hard and soft materials within this structure. They determined that the combination of hard and soft materials adheres significantly better to rough surfaces compared to structures produced from only a single soft material.

As a result, industrial handling processes can be improved and made safer, and that is not all. The materials are also promising in terms of on-skin applications, such as self-adhesive wound closures or “wearables” - networked computers that can be applied directly to the skin.

The scientists presented their findings in the renowned scientific journal *Applied Materials & Interfaces*. Co-author René Hensel is now going to receive the Adhesion Innovation Award in recognition of this publication. This award is co-organized by EURADH (European Adhesion Conference) and FEICA (Association of the European Adhesive & Sealant Industry).

As part of their investigations, the research scientists developed two-millimeter pillars as a model system and brought these into contact with rough surfaces. The measured force required to peel the pillar away again is the measure of the adhesion. “The pillars that we used were made of a hard material but their ends had a layer of soft plastic. In order to peel away this pillar, we needed to apply a force that was five times greater compared to peeling away a pillar composed entirely of the soft material. Therefore, it clearly adheres better,” explains René Hensel, the Deputy Head of the *Functional Microstructures* program division.

The research scientists established during the investigations that the quality of adhesion corresponds to the softness and thinness of the coating applied to the ends of the pillars. The softer the material, the better its ability to adapt to rough surfaces. The fact that adhesive strength correlates to how thin the coating is goes hand in hand with the delayed formation of cracks during

### CONTACT

INM – Leibniz Institute  
for New Materials  
Campus D2 2  
66123 Saarbrücken/Germany  
[www.leibniz-inm.de](http://www.leibniz-inm.de)

Dr. Carola Jung  
Press and Public Relations  
[carola.jung@leibniz-inm.de](mailto:carola.jung@leibniz-inm.de)  
Phone: +49681-9300-506  
Fax: +49681-9300-223

contact: The adhesive structure detaches from the surface whenever a crack forms. These cracks take longer to form due to reduced stress peaks. As a result, cracks and detachment only occur under higher loads. “Surprisingly, the thinner the coating is, the more pronounced this phenomenon,” adds Hensel. Adhesion is also affected by the shape - how two materials of varying hardness are combined. A rounded boundary layer between both materials improves adhesion. This also appears to affect the formation of cracks.

The thickness of the soft coating should simultaneously match the degree of roughness: “The surface of woodchip wallpaper is far rougher than skin, for instance, so in order for something to adhere to woodchip wallpaper, a much thicker soft coating must be selected compared to adhesion to skin,” says Hensel. The research scientists are currently very interested in adhesion to skin. This is central to future research as it appears to play a particularly important role in the development of “wearables” as well as for treating wounds.

Original publication:

Sarah C. L. Fischer, Eduard Arzt, and René Hensel, „Composite Pillars with a Tunable Interface for Adhesion to Rough Substrates”, *ACS Appl. Mater. Interfaces*, 2017, 9 (1), pp 1036–1044, DOI: 10.1021/acsami.6b11642; <https://pubs.acs.org/doi/10.1021/acsami.6b11642>

Your expert at INM:

Dr. René Hensel

Deputy Head *Functional Microstructures*

Phone: +49681-9300-390

[rene.hensel@leibniz-inm.de](mailto:rene.hensel@leibniz-inm.de)

INM – Leibniz Institute for New Materials, situated in Saarbrücken, is an internationally leading centre for materials research. INM conducts research and development to create new materials – for today, tomorrow and beyond. Research at INM is performed in three fields: *Nanocomposite Technology*, *Interface Materials*, and *Bio Interfaces*. INM is an institute of the Leibniz Association and has about 250 employees.